



Applications

- Used in mining, construction, engineering, power transmission fabrication, manufacturing, processing, marine
- Ideal for the assembly line, workstation, job site, workshop

Features

- Available in 0.25T, 0.5T and 1T.
- Standard lift height of 2.5 meters for 0.25T and 0.5T,3.0 meters for 1T. Optional lift heights available upon request.
- Ultra compact and lightweight.
- High-quality aluminum housing with non-protruding bolt.
- Heat-treated steel frame with bearings for gear and load wheel.
- Ompletely sealed brake and gear for added protection.
- Wide hook openings for easy installation and load attachment.
- Advanced overload limiter as standard equipment.
- Orrosion and abrasion-resistant nickel-plated load chain.
- Guided hook latch with tip supporting structure.
- Operating temperature from -40°C to +60°C.

Extremely lightweight, ultracompact and strong performance, this mini chain hoist is suitable for any situation that requires lifting with minimal effort and maximum safety.

Capacity: 250kg to 1T

KITO CX Series Chain Blocks

Specifications

Capa- city	Part No.	Model	Headroom	Standard Lifting Height	Hand Chain Length (folded)	Pull to Lift Full Load	Weight	Load Chain Diameter x Chain Falls	Load Chain Part No.	Dimensions in mm							
kg			mm	m	m	N	kg	mm		а	b	C	е	f	g	S	t
250	45377	CX003	217	2.5	2.0	147	2.4	3.2 x 1	44835	88	84	217	37	53	21	32	11
500	40322	CX005	260	2.5	2.0	187	4.5	4.3 x 1	40328	101	102	260	44	66	24.5	35.5	12
1,000	45380	CX010	360	3.0	2.5	193	7.3	4.3 x 2	40328	103	122	360	44	87	29	42.5	15

*Optional lift heights available.

Wide top & bottom hook openings

For easy installation and load attachment

Smart body with non-protruding bolts

Minimises the risk of damaging and operator injury during handling

Heat-treated steel frame

Steel frame with bearing for gear and load wheel. Ensures stable and safe rotation of gear and pinion shaft

CX003



Capacity
250kg

Mass
(Net weight) 2.4kg

CX005




Capacity
500kg
Mass
(Net weight) 4.5kg

CX010



Capacity
1000kg

Mass
(Net weight) 7.3kg



Nickel-plated load chain Breaking stress of 1000 N/mm²

Corrosion-resistant hand chain

Suitable for outdoor use

Twist checker as standard CX010

Enables a quick and easy check if the chain is twisted

Guided hook latch

with tip-supporting structure

Light, compact extremely powerful