

4H505P - Procedure Cart 5 Drawer

Features

- Adjustable push handle, quick & easy operation to enable users to set the push handle at the correct ergonomic height
- Corner buffers
- Diameter 125 anti-static total lock castors
- Raised drawer handles for grip & easy cleaning
- Epoxy powder coated frame
- Overall dimensions 535mm x 740mm x 1055mm (h)
- Large drawer for bottled medication & storage (depth = 190mm)
- Poly drawer dividers (4 sets)
- 5 drawers fitted with soft close runners & damper – prevents drawers from opening while in motion.
- Drawers accept most sachet drug dispensing systems (depth = 140mm)
- Slide out shelf fitted with runners for smooth, stable operation
- Lightweight composite aluminum/plastic panels, reduces cart noise while in motion and panels can be replaced economically if damaged
- Recessed ABS formed plastic top
- Removable wire basket
- IV pole
- Removable waste bin with lid

Sharps container holder (*container shown but not supplied)



| | |
|--------------------------------|---|
| Model | PSE12N-32 |
| Capacity (kg) | 1200kg |
| Mast Lift Height | 3200mm |
| Mast Stages | 2 |
| Lowered Mast Height | 82mm |
| Operator Type | Pedestrian |
| Fork Dimensions | 40 x 100 x 1150mm |
| Fork Length | 1150mm |
| Adjustable Base Legs I.D. | 980 - 1270mm |
| Adjustable Base Legs O.D. | 1170 - 1473mm |
| Turning Radius | 1345mm |
| Overall Width | 800mm |
| Drive Tire | 210 x 70mm polyurethane |
| Load Wheels | 84 x 70mm polyurethane |
| Lift Speed (Laden/Unladen) | 110/160 mm/s |
| Lowering Speed (Laden/Unladen) | 130/110 mm/s |
| Lift Motor | 2.2kw |
| Battery | 24V/60Ah LFP Lithium Battery with 24V/25A charger |
| Travel Speed | 4.2km/h(unloaded), 4.5km/h (fully loaded) |
| Parking Brake | Electromagnetic |

| | |
|--|------------------------------|
| Model | QPS124-35 |
| Drive | Battery |
| Operator Type | Pedestrian |
| Capacity | 1200kg |
| Load Centre Distance | 600mm |
| Service Weight (Without Battery) | 495kg |
| Battery Weight (Lithium Battery) | 20kg |
| Tires Material | PU |
| Front Tyre Size | 80x70mm |
| Rear Tyre Size | 210x70mm |
| Balance Wheels (Dimensions) | 150x50mm |
| Wheels, Number Front/Rear | 2/1 |
| Front Tread | 400mm |
| Rear Tread | 540mm |
| Lowered Mast Height | 2250mm |
| Mast Lift Height | 3500mm |
| Extended Mast Height | 3950mm |
| Height of Tiller in Drive Position Min./Max. | 880-1120mm |
| Height, Lowered | 90mm |
| Overall Length | 1750mm |
| Length to Face of Forks | 1125mm |
| Overall Width | 800mm |
| Outer Width of Leg | 1188-1470mm |
| Inner Width of Leg | 988-1270mm |
| Length of Leg | 1057mm |
| Fork Dimensions | 95/180/1125mm |
| Distance Between Fork-Arms | 240mm |
| Ground Clearance, Centre of Wheelbase | 35mm |
| Aisle Width for Pallets 1000x1200 Crossways | 2505mm |
| Aisle Width for Pallets 800x1200 Lengthways | 2250mm |
| Turning Radius | 1440mm |
| Travel Speed, Laden/Unladen | 3.5/4 km/h |
| Lift Speed, Laden/Unladen | 61/130mm/s |
| Lowering Speed, Laden/Unladen | 150/80mm/s |
| Max. Gradeability, Laden/Unladen | 3-7% |
| Service Brake | Electromagnetic |
| Drive Motor Rating | 2.2kW |
| Lift Motor Rating | 0.75kW |
| Battery Voltage, Nominal Capacity | Lithium battery 24V/50AH |
| Battery Size L x W x H | Lithium battery 330x90x180mm |
| Type of Control | DC-Speed Control |
| Sound Level at Driver's Ear acc. to EN12053 | <70dB(A) |