

## **CEXL121801 - Lifting Spreader Bar**

The CEXL121801 Crane Lifting Spreader Bar is a versatile piece of lifting equipment that can be used to lift long loads in two different ways. It can be used as a Lifting Beam by attaching the load to the centre single hook point, or as a Spreader Bar by securing the slings to the ends of the bar and on the hook of the crane or forklift jib.

This multi-tasking beam comes with several useful features, including adjustable load connection points that can be moved to three different positions by extending the arms. It also comes in 1200, 1500, and 1800mm load centres to provide flexibility for different load sizes.

Safety is a top priority when using the CEXL121801 Crane Spreader Bar. Safety pins are used to lock the extendable arms securely in position, and they are supplied with two safety swivel hooks as standard.

Moreover, this crane spreader bar is certified to the relevant Australian Standards, ensuring that it meets the highest safety and quality standards. The extendable arms have a zinc finish, while the main body has an enamel paint finish, making it highly durable and long-lasting.



Rated Capacity (RC)				Unit Weight
When Used As	Fully Re- tracted (LC1@200m m)	Middle Position (LC@1500mm)	Full Extended (LC@1800m m)	
	1275mm	1575mm	1875mm	55kg
Lifting Beam	3000kg	2000kg	1000kg	55kg
Spreader Bar	5000kg	5000kg	5000kg	55kg